


Audiophile Home Theater Performance Without The Big Speaker

Big Speaker Sound Without The Big Speaker®

Our latest generation represents a natural evolution of the product, plus the addition of audiophile-grade technologies that give the Blackstone® TL Series a truly sophisticated level of performance. Our top-of-the-line TL3 satellite and center epitomize the evolution of Polk®'s compact home theater series with a host of features that add something virtually all other comparably priced systems never offer: *truly astonishing home theater performance.*

TL3 Satellite & Center Channel Features

- **Time Lens™ Technology**—The acoustic centers of the tweeter and mid-bass driver are located in the same plane for superior imaging, while the acoustic lens incorporated in the grille smooths the tweeter's frequency response. The TL Series creates imaging and frequency balance previously impossible in small, high performance satellite speakers.



- **Extended Linear Motion (ELM) Voice Coil**—This motor structure design, incorporated in the 3 1/4" mid-bass driver, flattens the BL curve over a wider range of the driver's excursion, reducing distortion and extending dynamic range.
- **Steel-Reinforced Curved Enclosure Design**—Non-parallel surfaces, combined with the extra-rigid steel plates, not only results in a stronger and acoustically inert enclosure, but also produces less audible coloration from internal surface resonances.
- **PowerPort®** a patented Polk technology, extends the low frequency mid-bass driver response as it decreases air turbulence, eliminates "port noise" and bass output losses up to 3 dB.
- **3/4" Ring Radiator Tweeter**, used in our award-winning LS*i* and LC*i* Series speakers, delivers incredible accuracy and astonishing detail to beyond 30 kHz, even when listening off-axis.



- **Dynamic Balance® Driver Technology**, is Polk's patented solution to driver design that scientifically tunes materials to produce a flat frequency response, with sharp detail, transparency and the ability to play loud without strain.
- **3 1/4" Aerated Polypropylene Cone (APP)**, the same material used in our high-end freestanding speakers, is lightweight but stiff and strong, with longer linear excursion capabilities to play louder with less distortion.
- **Gold-Plated 5-Way Solid Metal Binding Posts** accept 14 gauge cable and offer hookup versatility and secure connections.
- **Hi-Gloss "Blackstone" Finish** matches today's most stylish flat panel TV's.

TL3 Specifications

	TL3 Satellite	TL3 Center
Frequency Response	90 Hz - 31 kHz	90 Hz - 31 kHz
Lower/Upper -3 dB limit	115 Hz - 28 kHz	115 Hz - 28 kHz
Nominal Impedance	8 Ohms	8 Ohms
Recommended Amp Power	10 - 125 W/channel	10 - 125 W/channel
Efficiency	88 dB	90 dB
Dimensions	7 3/4" H x 4 1/2" W x 5 15/16" D (19.69 cm x 11.43 cm x 15.08 cm)	4 5/16" H x 16 11/16" W x 3 15/16" D (10.95 cm x 42.37 cm x 10 cm)
Warranty	5 year parts & labor	5 year parts & labor

TL350 5 Pack	
System Components	(4) TL3 Sat, (1) TL3 Center
Frequency Response	85 Hz - 31 kHz
Lower/Upper -3 dB limit	115 Hz - 28 kHz
Nominal Impedance	8 Ohms
Recommended Amp Power	10 - 125 W/channel
Efficiency	90 dB
Dimensions	(see individual speakers for dimensions)
Warranty	5 year parts & labor

Specifications, dimensions and features subject to change without notice. For more information call us at 1-800-377-7655 (USA and Canada). Outside of North America call +1 (410) 358-3600.